

????????????? ????? ? ?????????????? TP400UVLS ?? 10??



Epoks?da sve?i



1,5 kg--28,00 EUR 3,0 kg-- 55,00 EUR 7,5 kg--128,00 EUR 15 kg--253,00 EUR 30 kg-- 497,00 EUR

Rating: Not Rated Yet

Price

[Ask a question about this product](#)

Description

TP400 UVLS IS A COLORLESS EPOXY RESIN WITH LONG TERM UV RESISTANCE. FOR MANUFACTURING CASTINGS UP TO 1 CM IN ONE LAYER

A two-component, general purpose, colorless structural epoxy resin with a UV blocker and HALS light stabilizer for molding, laminate, conglomerate, flooring and other industrial applications.

Characteristic:

low viscosity

Long-term UV resistance

Includes HALS light stabilizer

High transparency

Chemical and mechanical resistance

Simple Application

Product without solvents

A versatile product with a wide range of applications

Application:

For the installation of resin-quartz floors of filling and fused type.

For priming substrates under epoxy and polyurethane floors and coatings

Binder for the manufacture of epoxy-quartz screeds

Binder for the preparation of leveling mortars

For making glass and carbon laminates

For filling in 3D graphics

For a smooth fill

production time 20 min at 20 °C

Min air temperature 10 °?

Min resin temperature 15 °c

For perfect results, air and resin temperature 20°C

Available packages: Price with VAT EUR

1.5 kg--28.00 EUR

3.0 kg-- 55.00 EUR

7.5 kg--128.00 EUR

15 kg--253.00 EUR

30 kg-- 497.00 EUR