


POLYURETHANE FLOOR WITH SAND IN THE TECHNIART FLOOR SYSTEM TECHNOLOGY 500 PU (THICKNESS 1-2 MM) 1KV.M



Rating: Not Rated Yet

Price

Price with discount 16,90 €

[Ask a question about this product](#)

Description

POLYURETHANE FLOOR WITH SAND IN THE TECHNIART FLOOR SYSTEM TECHNOLOGY 500 PU (THICKNESS 1-2 MM)

A thin-coat floor made of colored polyurethane resin with natural quartz aggregate. Increased resistance to UV radiation. Perfect for the balcony and terrace.

THE SET INCLUDES:

Priming resin TECHNIPLAST 400 RST

Polyurethane resin dyed with TECHNIPLAST PU UVR-C in the selected color

Natural quartz aggregate

CONSUMPTION (given consumption applies to the execution of the floor on an even and undamaged surface)

For 5 m2:

TP 400 RST - 3 kg

TP 500 PU UVR-C - 8 kg

Sand 0.4-0.8 mm - 25 kg

For 10 m2:

TP 400 RST - 4.5 kg

TP 500 PU UVR-C - 12 kg

Sand 0.4-0.8 mm - 25 kg

For 15 m2:

TP 400 RST - 6 kg

TP 500 PU UVR-C - 20 kg

Sand 0.4-0.8 mm - 50 kg

For 20 m2:

TP 400 RST - 9 kg

TP 500 PU UVR-C - 24 kg

Sand 0.4-0.8 mm - 50 kg

For 25 m2:

TP 400 RST - 10.5 kg

TP 500 PU UVR-C - 32 kg

Sand 0.4-0.8 mm - 75 kg

For 30 m2:

TP 400 RST - 12 kg

TP 500 PU UVR-C - 36 kg

Sand 0.4-0.8 mm - 75 kg

available color:RAL: 1001, 1011, 1015, 3009, 6021, 7001, 7030, 7032, 7040, 7045, 7046, 7047, 1021,1015, 6001, 6011, 7035, 8017, 9003, 9005, 5024, 3001, 5023, 7024, 7038

Note: for light colors RAL 1001, 1021, 7032, 7035, 7047, 9003, 1021, apply at least three coats.

We offer materials and services for the installation of polymer floors