

TP200 Two-component colored epoxy 6.25kg

TECHNIPLAST

200



Rating: Not Rated Yet

Price

Price with discount 78,00 €

[Ask a question about this product](#)

Description

TECHNIPLAST 200 - COLOR EPOXY RESIN

Two-component colored epoxy resin for floors and coatings in the technique of painting, poured, as well as covered with quartz filler or colored flakes using the TECHNIArt FLOOR SYSTEM technology.

Characteristic:

attractive colors

high chemical and mechanical resistance,

ease of use,

solvent free product

APPLICATIONS:

car parks and garages,

Technical buildings,

utility room,

apartments,

offices,

warehouses,

industrial facilities,

government agencies,

office space, etc.

Examples of consumption in TECHNIArt FLOOR SYSTEM:

THIN-LAYER PAINTING SYSTEM 0.6-0.8 mm

PRIMER TECHNIPLAST 400 RST ~ 0.3-0.4 kg/m²

FIRST LAYER TECHNIPLAST 200 ~ 0.25 - 0.3 kg/m²

SECOND LAYER TECHNIPLAST 200 ~ 0.25 - 0.3 kg/m²

MATT VARNISH TECHNIPLAST 1000 (option) ~ 0.10 - 0.15 kg/m²

THIN-LAYER SYSTEM, COLORED WITH FLAKES 0.6-0.8 mm

PRIMER TECHNIPLAST 400 RST ~ 0.3-0.4 kg/m²

COVERING TECHNIPLAST 200 ~ 0.5-0.6 kg/.2

FILLING WITH COLOR FLAKES ~ 0.01 kg/m²

MATT VARNISH TECHNIPLAST 1000 (option) ~ 0.10 - 0.15 kg/m²

THIN LAYER SAND FLOOR (DIY OPTION) approx. 1.0–2.0 mm

LEVELING PRIMER TECHNIPLAST 400RST ~ 0.4-0.6 kg/m²

QUARTZ SAND FOR RESIN NQ 0.1-0.4 mm or NQ 0.8-1.2 mm - ratio 1:1 (by weight)

BASIC COATING TECHNIPLAST 200 ~ 0.3-0.4 kg/m²

FILLING WITH QUARTZ SAND NQ 0.4 - 0.8 mm or NQ 0.8-1.2 mm ~ 2.5 kg/m² (dry filling)

CLOSING COATING TECHNIPLAST 200 ~ 0.7 kg/m²

Available packages:

6.25 kg, 12.5 kg, 25 kg

Available colors:

RAL: 1001, 1011, 3009, 6021, 7001, 7030, 7032, 7040, 7045, 7046, 7047, 1021, 1015, 6001, 6011, 7035, 8017, 9003, 9005, 5024, 3001, 5023, 7024, 7038

Note: for light colors RAL 1001, 1021, 7032, 7035, 7047, 9003, 1021, apply at least three coats.